

## Tenda MW3 \* AC1200 dual band distribution mesh WiFi system 200m2 2PACKS

Šifra: 100601

Kategorija proizvoda: Ruteri, AP, Ekstenderi

Proizvođač: Tenda

**MpCena: 9.127,00 rsd.**

cena za odloženo plaćanje i kupovinu na rate

**Web Cena: 7.606,00 rsd.**

cena za web porudžbine i avansno plaćanje



MW3 is a 1200Mbps dual band distribution mesh WiFi system designed for 100-300? houses, bringing you with whole home WiFi coverage, as well as fast and stable internet connection. Pack of 3 provides you with up to 300? WiFi range; while pack of 2 provides you with up to 200? WiFi range. Compliant with IEEE 802.11v and IEEE 802.11r seamless roaming protocols, MW3 supports automatic network optimization and automatic routing selection, allowing you to enjoy more stable and flexible wireless network.

Standard&Protocol: IEEE802.3, IEEE802.3u

Interface: 2 Ethernet ports per mesh node

WAN and LAN on primary mesh node

Both act as LAN ports on additional mesh nodes

Antenna: 2\*3dBi internal dual band antennas

Button: 1 reset button

Power: Input:100-240V—50/60Hz

Dimension: 90 x 90 x 90mm

Wireless Standards: IEEE 802.11ac/a/n 5GHz

IEEE 802.11b/g/n 2.4GHz

Wireless Frequency2.4G: 2400MHz-2483MHz

5G: 5150MHz-5250MHz or 5725MHz-5825MHz

Data Rate: 5GHz: Up to 867Mbps

2.4GHz: Up to 300Mbps

Frequency: Simultaneous dual band 2.4GHz & 5GHz

Basic Features:SSID Broadcast

Beamforming

Wireless Security: Mixed WPA/WPA2-PSK(default)

Wireless roaming: Comply with IEEE802.11v/r

Internet Connection Type: PPPoE, Dynamic IP, Static IP, Bridge Mode

DHCP ServerDHCP Server

DHCP Client List

Virtual Server: Port Forwarding

UPnP

QoS: Support Smart QoS

Firewall: Forbid UDP flood attack

Forbid TCP flood attack

Forbid ICMP flood attack

DNS: Support manually setting DNS server

VPN: IPsec pass through

PPTP pass through

L2TP pass through

Other: Parental Control

Guest Network

Firmware upgrade online

Reset to factory settings

Setup Requirements: A mobile device running Android 4.0+ or iOS 8+

Temperature: Operating Temperature: 0° ~ 40°

Storage Temperature: -40° ~ 70°.

Humidity: Operating Humidity: 10% ~ 90% RH non-condensing

Storage Humidity: 5% ~ 90% RH non-condensing.

Certification: FCC, CE, RoHS, EAC, IC

Package Content: (2-pack) 2 identical mesh nodes

2 power adapters

Quick install guide

1 ethernet cable

**Uvek smo ovde i tako već 20 godina!**

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.