

Firma: Link računari doo Adresa: Kneza Lazara 35 Telefon: +381 35-245-245 Fax: +381 65-245-245-8

PIB: 106628389

E-mail: office@linkplus.rs

Tenda MW5S (2 pack) AC1200 dual band 2.4+5GHz distribution mesh WiFi system 230m2

Šifra: 107413


Kategorija prozivoda: Ruteri, AP, Ekstenderi

Proizvođač: Tenda

MpCena: 10.444,00 rsd.

cena za odloženo plaćanje i kupovinu na rate

Web Cena: 8.704,00 rsd. cena za web porudžbine i avansno plaćanje





Powered by Tenda's proprietary mesh technology, each node automatically connects to the other, creating a distributed network throughout your entire home. A 2-pack of nova MW5s covers up to 2500 square feet. Go big and easily expand your WiFi network in the future simply by adding nodes.

Two power amplifiers for each band to enhance the whole WiFi coverage

Two power amplifiers used both on 2.4 GHz and 5 GHz bands of the primary node to enhance the signal strength and receiving capability, helping the nova MW5s outperform ordinary routers.

Built-in dual band antennas for excellent wall penetration capability

With features that optimize both the 2.4 GHz and 5 GHz bands, the nova MW5s system automatically adjusts the data rates when it works behind multiple walls.

Beamforming technology concentrates the signal for better wall penetration

Powered by Beamforming technology, the nova MW5s projects a stronger WiFi signal in a direction where your devices are located. Instead of just broadcasting signals to a wide area, Tenda's Beamforming concentrates the signal and aims it directly at the target.

Automatic networking makes setup a breeze

All nodes are delivered pre-paired right out of the box, making the system easy to setup and an ideal choice for whole home WiFi coverage.

Supports up to 80 devices

Combining the 1 GHz main chip with MU-MIMO technology, the nova MW5s communicates simultaneously with multiple devices, ensuring a lag-free internet connection when you enable the Capacity-oriented Mode using the App.

Standard&Protocol IEEE802.11a/b/g/n/ac

IEEE 802.3, IEEE 802.3u, IEEE 802.4ab

Ethernet Ports Primary Node: 2 x 10/100/1000Mbps RJ45 ports

Secondary Node: 2 x 10/100Mbps RJ45 ports

Antenna2 x Internal antenna Button1 x Reset Button

Power Primary Node Input: 100-240V—50/60Hz, 0.6A



Output: 12V1A

Secondary Node Input: 100-240V-50/60Hz, 0.3A

Output: 9V1A

Dimension 91 x 91 x 93mm (3.58 x 3.58 x 3.66 in.)

LED indicator1 x Tri-color LED Indicator(Green, Yellow, Red) Wireless Standards IEEE802.11a/b/g/n/ac (WiFi 5 wave 2)

Wireless roamingComply with IEEE802.11k/v/r

Mesh network StandardIEEE802.11s

Rate2.4GHz: 300Mbps

5GHz: 867Mbps

Frequency2.4~2.4835GHz

5.15~5.25GHz 5.725~5.85GHz Transmit PowerCE:

Basic FeaturesSSID Broadcast

Beam Forming MU-MIMO

Wireless SecurityWPA-PSK/WPA2-PSK(default)

Operating ModeRouter Mode, Bridge Mode

Internet Connection TypePPPoE, Dynamic IP, Static IP, PPPoE(Russia), PPTP(Russia), L2TP(Russia)

DHCP ServerDHCP Server, DHCP Client List

Virtual ServerPort Forwarding, UPnP

Parental ControlClient Filter

FirewallForbid TCP/UDP flood attack

VPNPPTP/L2TP/IPsec pass through DNSSupport manually setting DNS server

Special Features Smart QoS (Gaming, Video & Audio, Download)

Software OtherAuto-sensing internet connection

Support App management and Remote management

Guest Network

Firmware upgrade online

Operation Temperature $0 \sim 40$?

Storage Temperature -40 ~ 70 ?

Operating Humidity 10%~90% RH non-condensing

Storage Humidity 5%~90% RH non-condensing

APP installation Available in iOS 8.0 or later, Android 4.0 or later

Certification CE, FCC, RoHS, EAC, IC

Package Content Mesh5 x 1, Mesh3f x 1, Power adapter x 2, QIG x 1, RJ45 Gigabit Ethernet cable x 1

Uvek smo ovde i tako već 20 godina!