

LAN Router TP-LINK TL-WR840N WiFi 300Mbps

Šifra: 120711

Kategorija proizvoda: Ruteri, AP, Ekstenderi

Proizvođač: TP-Link

MpCena: 3.158,00 rsd.

cena za odloženo plaćanje i kupovinu na rate

Web Cena: 2.632,00 rsd.

cena za web porudžbine i avansno plaćanje



HARDWARE FEATURES	
Interface	4 10/100Mbps LAN PORTS 1 10/100Mbps WAN PORT
Button	WPS/RESET Button
Antenna	2 Antennas
External Power Supply	9VDC / 0.6A
Wireless Standards	IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Dimensions (W x D x H)	7.2 x 5.0 x 1.4in.(182 x 128 x 35 mm)
WIRELESS FEATURES	
Frequency	2.4-2.4835GHz
Signal Rate	11n: Up to 300Mbps(dynamic) 11g: Up to 54Mbps(dynamic) 11b: Up to 11Mbps(dynamic)
Reception Sensitivity	270M: -68dBm@10% PER 130M: -68dBm@10% PER 108M: -68dBm@10% PER 54M: -68dBm@10% PER 11M: -85dBm@8% PER 6M: -88dBm@10% PER 1M: -90dBm@8% PER
Transmit Power	CE: <20dBm FCC: <30dBm
Wireless Functions	Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
Wireless Security	64/128-bit WEP, WPA / WPA2,WPA-PSK / WPA2-PSK
SOFTWARE FEATURES	
Quality of Service	WMM, Bandwidth Control
WAN Type	Dynamic IP/Static IP/PPPoE/ PPTP/L2TP
Management	Access Control Local Management Remote Management
DHCP	Server, Client, DHCP Client List, Address Reservation
Port Forwarding	Virtual Server,Port Triggering, UPnP, DMZ
Dynamic DNS	DynDns, Comexe, NO-IP
VPN Pass-Through	PPTP, L2TP, IPSec (ESP Head)

SOFTWARE FEATURES

Access Control	Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security	DoS, SPI Firewall IP Address Filter/MAC Address Filter/Domain Filter IP and MAC Address Binding
Protocols	Support IPv4 and IPv6
Guest Network	2.4GHz Guest Network x1
OTHERS	
Certification	CE, RoHS
Package Contents	Wireless N Router TL-WR840N Power supply unit Resource CD Ethernet Cable Quick Installation Guide
System Requirements	Windows 2000/XP/Vista™, Windows 7, Windows 8, Windows 8.1, Windows 10 or Mac OS or Linux-based operating system
Environment	Operating Temperature: 0?40? (32104) Storage Temperature: -40?70? (-40158) Operating Humidity: 10%90% non-condensing Storage Humidity: 5%90% non-condensing

Uvek smo ovde i tako već 20 godina!