Firma: Link računari doo
Adresa: Kneza Lazara 35
Telefon: +381 35-245-245
Fax: +381 65-245-245-8
PIB: 106628389
E-mail: office@linkplus.rs

Matična ploča AM4 Gigabyte A520M H



Šifra: 121663
Kategorija prozivoda: Matične ploče
Proizvođač: GIGABYTE

MpCena: 10.260,00 rsd.

cena za odloženo plaćanje i kupovinu na rate

Web Cena: 8.550,00 rsd.

cena za web porudžbine i avansno plaćanje

Tip procesora:	AMD
Podnožje:	AMD® AM4
Čipset:	AMD A520
Format ploče:	Micro ATX
Podržani procesori:	AMD Socket AM4, support for: AMD Ryzen™ 5000 Series Ryzen™ 5000 G-Series Ryzen™ 4000 G-Series and Ryzen™ 3000 Series Processors
Podržana memorija:	DDR4
Memorija:	2 x DDR4 DIMM sockets supporting up to 64 GB (32 GB single DIMM capacity) of system memory Support for DDR4 5100(O.C.) 4800(O.C.) 4600(O.C.) 4400(O.C.) 4266(O.C.) 4133(O.C.) 4000(O.C.) 3866(O.C.) 3733(O.C.) 3600(O.C.) 3466(O.C) 3400(O.C.) 3200 2933 2667 2400 2133 MHz memory modules Dual channel memory architecture Support for ECC Un-buffered DIMM 1Rx82Rx8 memory modules* * ECC memory (ECC mode) support varies by CPU Support for non-ECC Un-buffered DIMM 1Rx82Rx81Rx16 memory modules Support for Extreme Memory Profile (XMP) memory modules
Slotovi za proširenje:	CPU: 1 x PCI Express x16 slot, supporting PCIe 3.0 and running at x16 Chipset: 2 x PCI Express x1 slots, supporting PCIe 3.0
Storage:	CPU: 1 x M.2 connector (Socket 3, M key, type 224222602280 SATA and PCIe 3.0 x4x2 SSD support) Chipset: 4 x SATA 6Gbs connectors Support for RAID 0, RAID 1, and RAID 10
Mrežna karta:	Realtek® GbE LAN chip (1

Gbit100 Mbit)	
Zvučna karta:	Realtek® Audio CODEC High Definition Audio 245.17.1-channel
USB:	CPU: 4 x USB 3.2 Gen 1 ports on the back panel Chipset: 2 x USB 3.2 Gen 1 ports available through the internal USB header 6 x USB 2.01.1 ports (2 ports on the back panel, 4 ports available through the internal USB headers)
Konektori na zadnjoj strani:	1 x PS2 keyboardmouse port 1 x DVI-D port 1 x HDMI port 4 x USB 3.2 Gen 1 ports 2 x USB 2.01.1 ports 1 x Q-Flash Plus button 1 x RJ-45 port 3 x audio jacks
Interni konektori:	1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector 1 x CPU fan header 2 x system fan headers 1 x addressable LED strip header 1 x RGB LED strip header 1 x M.2 Socket 3 connector 4 x SATA 6Gbs connectors 1 x front panel header 1 x front panel audio header 1 x speaker header 1 x USB 3.2 Gen 1 header 2 x USB 2.01.1 headers 1 x Trusted Platform Module (TPM) header (2x6 pin, for the GC-TPM2.0_S module only) 1 x serial port header 1 x chassis intrusion header 1 x Clear CMOS jumper
Bios:	1 x 128 Mbit flash Use of licensed AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Razno:	{"url":"","title":"","target":""}

Uvek smo ovde i tako već 20 godina!

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.