

Matična ploča 1200 Asus PRIME H510M-R-SI

Šifra: 124277

Kategorija proizvoda: Matične ploče

Proizvođač: ASUS

MpCena: 10.597,00 rsd.

cena za odloženo plaćanje i kupovinu na rate

Web Cena: 8.831,00 rsd.

cena za web porudžbine i avansno plaćanje



Tip procesora:	Intel
Podnožje:	Intel®; 1200
Čipset:	Intel H510
Format ploče:	Micro ATX
Podržani procesori:	Intel® Socket LGA1200 for 11th Gen Intel® Core™ Processors & 10th Gen Intel® Core™, Pentium® Gold and Celeron® Processors
Podržana memorija:	DDR4
Memorija:	2x DIMM, MAX. 64 GB
Integrisana grafička karta:	Integrated Graphics Processor * 1 x D-Sub 1 x DVI-D 1 x HDMI 1.4b *Graphics specifications may vary between CPU types.
Slotovi za proširenje:	Intel® 10th Gen Processors 1 x PCIe 3.0 x16 (x16 mode) Intel® H410 Chipset 2 x PCIe 3.0 x1
Storage:	Total supports 1 x M.2 slots and 4 x SATA 6Gbps ports Intel® H410 Chipset : 1 x M.2 Socket 3, with M Key, type 224222602280 storage devices support (SATA & PCIE 3.0 X2 mode)*1 4 x SATA 6Gbps port(s)
Mrežna karta:	Realtek® RTL8111H
Zvučna karta:	Realtek ALC887 7.1-Channel High Definition Audio CODEC *2 - Supports : Jack-detection, Multi-streaming, Front Panel Jack-retasking, up to 24-Bit192kHz playback Audio Feature : - LED-illuminated design - Audio Shielding - Dedicated audio PCB layers - Premium Japanese audio capacitors
USB:	Rear USB Port (Total 4) 2 x USB 3.2 Gen 1 port(s)(2 x Type-A) 2 x USB 2.0 port(s)(2 x Type-A) Front USB Port (Total 6) 2 x USB 3.2 Gen 1 port(s) 4 x USB 2.0 port(s)
Konektori na zadnjoj strani:	2x USB 3.2 Gen1 2x USB 2.0 ports 2x PS2 1x D-Sub 1x DVI-D

1x Realtek 1Gb Ethernet 3x Audio
jacks

Interni konektori:

1 x CPU Fan connector(s) 2 x
Chassis Fan connector(s) 1 x USB
3.2 Gen 1(up to 5Gbps)
connector(s) support(s)
additional 2 USB 3.2 Gen 1
port(s) 2 x USB 2.0 connector(s)
support(s) additional 4 USB 2.0
port(s) 1 x M.2 Socket 3 with M
Key, type 224222602280 storage
devices support (SATA & PCIE
3.0 X2 mode) 1 x SPI TPM header
1 x COM port(s) connector(s) 4 x
SATA 6Gbs connector(s) 1 x
SPDIF out header(s) 1 x 24-pin
EATX Power connector(s) 1 x 8-
pin EATX 12V Power connectors
1 x Front panel audio
connector(s) (AAFP) 1 x Clear
CMOS jumper(s) 1 x System
panel connector 1 x Speaker
connector

Bios:

128 Mb Flash ROM, UEFI AMI BIOS

Razno:

{"url":"","title":"","target":""}

Uvek smo ovde i tako već 20 godina!