

MB AM4 ASUS PRIME B450M-A II

Šifra: 128446

Kategorija proizvoda: Matične ploče

Proizvođač: ASUS

MpCena: 10.864,00 rsd.

cena za odloženo plaćanje i kupovinu na rate

Web Cena: 9.053,00 rsd.

cena za web porudžbine i avansno plaćanje



Podnožje	AMD® AM4
Čipset	AMD® B450
Tip procesora	AMD
Format ploče	Micro ATX
Podržani procesori	AMD AM4 Socket for 3rd/2nd/1st Gen AMD Ryzen /2nd and 1st Gen AMD Ryzen with Radeon Vega Graphics Processors
Podržana memorija	DDR4
Memorija	3rd/2nd/1st Gen AMD Ryzen / 2nd and 1st Gen AMD Ryzen with Radeon Vega Graphics/ Athlon with Radeon Graphics : 1 x DIMM, Max. 128GB, DDR4 4400(O.C.)/4000(O.C.)/3866(O.C.)/3733(O.C.)/3600(O.C.)/3466(O.C.)/3400(O.C.)/3300(O.C.)/3200(O.C.) MHz Un-buffered Memory Dual Channel Memory Architecture ECC Memory (ECC mode) support varies by processor
Integrirana grafička karta	Integrated Graphics in the 2nd and 1st Gen AMD Ryzen with Radeon Vega Graphics/ Athlon with Radeon Graphics : 1 x DVI-D 1 x HDMI 2.0b
Slotovi za proširenje	3rd/2nd/1st Gen AMD Ryzen Processors 1 x PCIe 3.0 x16 (x16 mode) 2nd and 1st Gen AMD Ryzen with Radeon Graphics Processors 1 x PCIe 3.0 x16 (x8 mode) AMD Athlon with Radeon Vega Graphics Processors 1 x PCIe 3.0 x16 (x4 mode)
Skladište	Total supports 1 x M.2 slot(s) and 6 x SATA 6Gb/s ports 3rd/2nd/1st Gen AMD Ryzen™ / 2nd and 1st Gen AMD Ryzen with Radeon™ Vega Graphics : 1 x M.2 Socket 3, with M key, type 2242/2260/2280/22110 storage devices support (SATA & PCIe 3.0 x 4 mode) AMD Athlon with Radeon™ Vega Graphics Processors : 1 x M.2 Socket 3, with M key, type 2242/2260/2280/22110 storage devices support (SATA & PCIe 3.0 x 4 mode) 3rd/2nd/1st Gen AMD Ryzen™ / 2nd and 1st Gen AMD Ryzen™ with Radeon™ Vega Graphics/ Athlon with Radeon Graphics Processors : 2 x SATA 6Gb/s port(s), Support Raid 0, 1, 10 AMD B450 chipset : 4 x SATA 6Gb/s port(s)
Mrežna karta	Realtek® RTL8111H ASUS LANGuard
Zvučna karta	Realtek ALC887/897 7.1-Channel High Definition Audio CODEC - Supports : Jack-detection, Multi-streaming, 24-Bit/192kHz playback Audio Feature : - LED-illuminated design - Audio Shielding - Dedicated audio capacitors
USB	Rear USB Port (Total 6) 2 x USB 3.2 Gen 2 (up to 10Gbps) port(s)(2 x Type-A) 4 x USB 3.2 Gen 1 port(s) (2 x Type-A) 2 x USB 3.2 Gen 1 port(s) 4 x USB 2.0 port(s)
Konektori na zadnjoj strani	1 x PS/2 keyboard/mouse combo port(s) 1 x DVI-D 1 x D-Sub 1 x HDMI 1 x LAN (RJ45) port(s) 2 x USB 3.2 Gen 1 (blue) Type-A 3 x Audio jack(s) 1 x BIOS FlashBack Button(s)
Interni konektori	1 x CPU Fan connector(s) (1 x 4 -pin) 2 x Chassis Fan connector(s) (2 x 4 -pin) 1 x USB 3.2 Gen 1 (up to 10Gbps) port(s) (19-pin) 2 x USB 2.0 connector(s) support(s) additional 4 USB 2.0 connector(s) 2242/2260/2280/22110 storage devices support (SATA & PCIE 3.0 x 4 mode) 1 x SPI TPM header 1 x SATA 6Gb/s connector(s) 1 x S/PDIF out header(s) 1 x 24-pin EATX Power connector(s) 1 x 8-pin ATX 12V Power connector(s) (AAFP) 1 x System panel(s) 1 x Clear CMOS jumper(s) 1 x COM port header 1 x Speaker header
BIOS	256 Mb Flash ROM, UEFI AMI BIOS

Uvek smo ovde i tako već 20 godina!

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virtumanski - bezgotovinski.